

AIR-EXCEL
OFFSET BLANKET

MC5000R

Feature / Benefit

1. **Improved surface rubber compound**
   provides excellent ink transfer and solid coverage for both coated and uncoated paper stocks.
2. **Strong construction with unique compressible layer**
   offered excellent smash resistance and extended durability.
3. **The unique combination**
   of the improved surface rubber and its profile assures stable metal release and high reproductivity of metal decorating.

Technical Data

● Surface	
Rubber Compound	For conventional ink type
Finish	Ground
Color	Green
● Construction	
Compressible Layer	Closed Cell
Nominal Thickness/ply	1.95mm/3ply
	1.68mm/3ply
	1.30mm/2ply
● Application	
	Metal decorating
	Packaging printing
● Physical Property of 1.95mm Type	
Thickness	1.93 - 1.98mm
Tensile Strength at Break	74N/mm<
Elongation at 10N/mm	0.9%>
Roughness <Ra>	Approx. 1.7μm
Compressibility	Hard

ROUGH — SMOOTH

HARD — SOFT

kinyo

KINYOSHA CO., LTD.
6F Art Village Osaki Central Tower,
1-2-2, Osaki, Shinagawa-ku, Tokyo, 141-0032 JAPAN
Tel. International +81-(0)3-5745-6250
Fax. +81-(0)3-5745-6260
overseasales@kinyo-j.co.jp

ISO 9001・ISO14001 Certified.

www.kinyo-j.co.jp

The trademark of "Kinyo" and any other product names, technical names are trademarks or registered trademarks of KINYOSHA CO., LTD. or any of its affiliates.

Dealer:

HG07198-01-201406